

# Package ‘sendgridr’

November 6, 2022

**Title** Mail Sender Using 'Sendgrid' Service

**Version** 0.6.1

**Description** Send email using 'Sendgrid' <<https://sendgrid.com/>>  
mail API(v3) <[https://docs.sendgrid.com/api-reference/  
how-to-use-the-sendgrid-v3-api/authentication](https://docs.sendgrid.com/api-reference/how-to-use-the-sendgrid-v3-api/authentication)>.

**License** MIT + file LICENSE

**URL** <https://github.com/mrchypark/sendgridr>

**BugReports** <https://github.com/mrchypark/sendgridr/issues>

**Imports** magrittr, httr, jsonlite, usethis, cli, base64enc, emayili (>= 0.7), keyring

**Encoding** UTF-8

**RoxygenNote** 7.2.1

**Depends** R (>= 3.4)

**Suggests** covr, testthat

**NeedsCompilation** no

**Author** Chanyub Park [aut, cre] (<<https://orcid.org/0000-0001-6474-2570>>)

**Maintainer** Chanyub Park <[mrchypark@gmail.com](mailto:mrchypark@gmail.com)>

**Repository** CRAN

**Date/Publication** 2022-11-06 19:00:02 UTC

## R topics documented:

address	2
attachments	3
auth_check	3
auth_set	4
body	4
dynamic_template	5
dynamic_template_data	5
embed_rmd	6

from . . . . .	7
mail . . . . .	7
print.sg_mail . . . . .	8
send . . . . .	8
subject . . . . .	9
template_id . . . . .	10

<b>Index</b>	<b>11</b>
--------------	-----------

---

address	<i>set address to sg_mail class</i>
---------	-------------------------------------

---

### Description

to(), cc(), bcc() is for set email address to sg\_mail class

### Usage

```
to(sg_mail, email, name = "")
```

```
cc(sg_mail, email, name = "")
```

```
bcc(sg_mail, email, name = "")
```

### Arguments

sg\_mail (required)mail object from package

email (required)email address

name (optional)name for email address.

### Value

sg\_mail class with mail address.

### Examples

```
mail() %>%
  to("mrchypark@gmail.com")
```

```
mail() %>%
  cc("mrchypark@gmail.com")
```

```
mail() %>%
  bcc("mrchypark@gmail.com")
```

attachments                      *attachments*

**Description**

attachments

**Usage**

attachments(sg\_mail, path, name, content\_id)

**Arguments**

sg\_mail                      (required)mail object from package  
 path                          (required)file path to attach  
 name                          file name. default is path's file name  
 content\_id                   content id. default is Null.

**Value**

sg\_mail class with attachments.

**Examples**

```
path <- system.file("extdata", "test.Rmd", package = "sendgridr")
mail() %>%
  attachments(path)
```

auth\_check                      *Check API key for auth.*

**Description**

Check API key for auth.

**Usage**

auth\_check()

**Value**

TRUE/FALSE check work fine return TRUE.

---

auth_set	<i>Set API key for auth.</i>
----------	------------------------------

---

**Description**

Set API key for auth.

**Usage**

```
auth_set(apikey)
```

**Arguments**

apikey	sendgrid api key. If key has value, just use as api key. If without param, function call interactive prompt input.
--------	--

**Value**

None

---

body	<i>body</i>
------	-------------

---

**Description**

body

**Usage**

```
body(sg_mail, body, type = "text/html")
```

**Arguments**

sg_mail	(required)mail object from package
body	(required)mail content html support.
type	content type. text/html is default.

**Value**

sg\_mail class with body content.

**Examples**

```
mail() %>%
  body("mrchypark@gmail.com")
```

---

dynamic\_template      *Add dynamic template*

---

### Description

Create dynamic templates at <https://mc.sendgrid.com/dynamic-templates>.

### Usage

```
dynamic_template(sg_mail, template_id, template_data, force = FALSE)
```

### Arguments

sg\_mail            (required) mail object from package

template\_id        (required) template\_id start "d-" and 32-length only digit and lower case alpha-bet like "d-4ad23ad40a0e47d0a0232b85f24ca5c2"

template\_data     A key-value list for template data. (See <https://docs.sendgrid.com/ui/sending-email/how-to-send-an-email-with-dynamic-templates>)

force              pass template\_id validation. default is FALSE.

### Value

sg\_mail class with dynamic template

### Examples

```
mail() %>%
  dynamic_template("d-4ad23ad40a0e47d0a0232b85f24ca5c2", list(first_name = "Amanda", link = "foo"))

mail() %>%
  dynamic_template(template_id = "foo",
    template_data = list(first_name = "Amanda", link = "foo"),
    force = TRUE)
```

---

dynamic\_template\_data      *Add dynamic template data*

---

### Description

template\_id must be included for this data to be applied.

### Usage

```
dynamic_template_data(sg_mail, data)
```

**Arguments**

`sg_mail` (required) mail object from package  
`data` A key-value list for template data. (See <https://docs.sendgrid.com/ui/sending-email/how-to-send-an-email-with-dynamic-templates>)

**Value**

`sg_mail` class with template data for dynamic transactional templates

**Examples**

```
data_lst <-  
  list(  
    first_name = "Amanda",  
    link = "foo"  
  )  
  
mail() %>%  
  template_id("d-4ad23ad40a0e47d0a0232b85f24ca5c2")%>%  
  dynamic_template_data(data_lst)
```

---

embed\_rmd

*Embedding Rmd on body with images.*

---

**Description**

Embedding Rmd on body with images.

**Usage**

```
embed_rmd(sg_mail, input, ...)
```

**Arguments**

`sg_mail` (required) mail object from package  
`input` (required) input file path to render for email.  
`...` extra params pass to `emayili::render()` function.

**Examples**

```
path <- system.file("extdata", "test.Rmd", package = "sendgridr")  
mail() %>%  
  embed_rmd(path)
```

---

from	<i>from</i>
------	-------------

---

**Description**

from

**Usage**

```
from(sg_mail, email, name = "")
```

**Arguments**

sg_mail	(required)mail object from package
email	(required)email address
name	name for email address

**Value**

sg\_mail class with from mail address.

**Examples**

```
mail() %>%  
  from("mrchypark@gmail.com")
```

---

mail	<i>Set mail class for Sendgrid</i>
------	------------------------------------

---

**Description**

New mail class for sendgrid.

**Usage**

```
mail()
```

**Value**

sg\_mail class.

**Examples**

```
mail()
```

`print.sg_mail`            *Print for sg\_mail class*

---

### Description

Print for sg\_mail class

### Usage

```
## S3 method for class 'sg_mail'  
print(x, ...)
```

### Arguments

`x`                    `sg_mail` class object  
`...`                pass for default print. But not use in `sg_mail` class.

---

`send`                    *send mail*

---

### Description

Send mail with mail content.

### Usage

```
send(mail)
```

### Arguments

`mail`                mail object

### Value

[list](https://docs.sendgrid.com/api-reference/how-to-use-the-sendgrid-v3-api/authentication) if success, success message. and error, please check <https://docs.sendgrid.com/api-reference/how-to-use-the-sendgrid-v3-api/authentication>.

### Examples

```
## Not run:  
  
data_lst <-  
  list(  
    total = "$239.85",  
    name = "Sample Name"  
  )
```

```
mail() %>%
  from("example1@mail.com", "example name for display") %>%
  to("example2@mail.com", "example name for display 2") %>%
  dynamic_template_data(data_lst) %>%
  template_id(template_id) %>%
  subject("test mail title") %>%
  body("hello world!") %>%
  ## attachments is optional
  attachments("report.html") %>%
  send()

## End(Not run)
```

---

subject

*subject*

---

## Description

subject

## Usage

```
subject(sg_mail, subject)
```

## Arguments

sg_mail	(required)mail object from package
subject	(required)mail subject

## Value

sg\_mail class with subject.

## Examples

```
mail() %>%
  subject("mrchypark@gmail.com")
```

---

template_id	<i>template id</i>
-------------	--------------------

---

**Description**

Create dynamic templates at <https://mc.sendgrid.com/dynamic-templates>

**Usage**

```
template_id(sg_mail, template_id, force = FALSE)
```

**Arguments**

sg_mail	(required) mail object from package
template_id	(required) template_id start "d-" and 32-length only digit and lower case alpha-bet like "d-4ad23ad40a0e47d0a0232b85f24ca5c2"
force	pass template_id validation. default is FALSE.

**Value**

sg\_mail class with template id.

**Examples**

```
mail()%>%  
  template_id("d-4ad23ad40a0e47d0a0232b85f24ca5c2")
```

```
mail() %>%  
  template_id("foo", force = TRUE)
```

# Index

address, [2](#)  
attachments, [3](#)  
auth\_check, [3](#)  
auth\_set, [4](#)  
  
bcc (address), [2](#)  
body, [4](#)  
  
cc (address), [2](#)  
  
dynamic\_template, [5](#)  
dynamic\_template\_data, [5](#)  
  
embed\_rmd, [6](#)  
  
from, [7](#)  
  
list, [8](#)  
  
mail, [7](#)  
  
print.sg\_mail, [8](#)  
  
send, [8](#)  
subject, [9](#)  
  
template\_id, [10](#)  
to (address), [2](#)