

The `prelim2e` package

Martin Schröder*

November 24, 2020

Abstract

This package allows the marking of (preliminary) versions of a document on the output.

Contents

| | | |
|----------|--|----------|
| 1 | Introduction | 1 |
| 2 | Requirements | 1 |
| 3 | Usage | 2 |
| 4 | Options | 2 |
| 5 | Required packages | 3 |
| 6 | Putting more things at the bottom | 3 |
| 7 | Acknowledgements | 3 |
| | Change History | 3 |

1 Introduction

This package allows the marking of (preliminary) versions of a document. This is done using the command `\PrelimText`, whose expansion is added *below the footer* of every page of a document (look at the bottom of this page for an example).

2 Requirements

Version 2.00 requires the kernel hook management and is no longer useable with LaTeX versions older than 2020/10/01. In case you have any understandable reason, which requires the old implementation, feel free to contact the maintainer.

*maintained by Marei Peischl <marei@peitex.de>

3 Usage

Simply using this package via `\usepackage{prelim2e}` produces a text in the form of “Preliminary version – November 24, 2020”.

| | |
|---|--|
| <code>\PrelimText</code> <code>\PrelimWords</code> | <p>The text is produced by the commands <code>\PrelimText</code> and <code>\PrelimWords</code>, which can be changed via <code>\renewcommand</code> or by using options at the <code>\usepackage</code> command (see section 4).</p> <p>The footer for this documentation was produced by changing <code>\PrelimWords</code> to</p> <pre> \renewcommand*{\PrelimWords}{% \textsf{prelim2e} package -- Version \fileversion -- Documentation \LaTeX{}ed% } </pre> |
|---|--|

`\PrelimTextStyle`

The style of the Text can be controlled by `\PrelimTextStyle`. This can also be adjusted using `\renewcommand*`. The default is set empty, but will use the default font in footnotesie.

4 Options

The package has the following options:

| | |
|---|---|
| New feature 2001/02/17 | <p><code>danish</code> This sets the text to “Foreløbig version”. It does not use the <code>babel</code> package.</p> <p><code>draft</code> If this option is used a text appears below the normal pagebody. It is the default.</p> <p><code>final</code> If this option is used <code>prelim2e</code> produces no text.</p> <p><code>english</code> This sets the text to “Preliminary version”. It is the default.</p> |
| New feature 1997/05/12 | <p><code>french</code> This sets the text to “Version préliminaire”. It does not use the <code>french</code> or <code>babel</code> package.</p> <p><code>german</code> This sets the text to “Vorläufige Version”. It does not use the <code>german</code> or <code>babel</code> package.</p> |
| New feature 2001/02/17 New feature 2009/05/29 New description 1997/05/12 | <p><code>italian</code> This sets the text to “Versione preliminare”. It does not use the <code>babel</code> package.</p> <p><code>norsk</code> This sets the text to “Foreløpig versjon”. It does not use the <code>babel</code> package.</p> <p><code>time</code> This adds the time at the beginning of the current <code>L^AT_EX</code> to the text. The time is produced using the <code>\thistime</code> command, which may be provided by the <code>scrttime</code> package^[2]. If you don’t use the <code>scrttime</code> package (e. g. by specifying the <code>scrttime</code> option), you must provide it yourself or by some other package.</p> |
| New feature 1997/05/12 | <p><code>scrttime</code> This loads the <code>scrttime</code> package^[2] (part of the KOMA-Script bundle), which provides the <code>\thistime</code> command used by the <code>time</code> option. The <code>scrttime</code> option implies the <code>time</code> option.</p> <p>All other options are passed to the <code>scrttime</code> package if the <code>scrttime</code> option is selected.</p> |

5 Required packages

The package requires the following packages:

New description
1997/05/12

`scrtime`[2] It is used to typeset the current time and is needed if the `scrtime` option is selected.

6 Putting more things at the bottom

Another package you might like to use with `prelim2e` is `vrslon`[3]. This allows the definition and maintenance of a version number like 3.14159 *within* \LaTeX , which can be put at the bottom of every page using `prelime2e`.

7 Acknowledgements

The idea of this package is based on `prelim.sty`[1] for \LaTeX 2.09 by Robert Tolksdorf (`tolk@cs.tu-berlin.de`). It provides nearly the same functionality as `prelim2e`, but in a very dirty way: it uses a modified output routine and does not work with \LaTeX 2 ϵ .

The time functionality now uses the `scrtime` package by Markus Kohm (`markus.kohm@gmx.de`).

Rowland Bartlett (`R.BARTLETT@liverpool-john-moores.ac.uk`) brought forth the idea of separating the time option and the `scrtime` package; Daniel Courjon (`dcourjon@utinam.univ-fcomte.fr`) provided the text for the french option, Arne Jørgensen (`arne.jorgensen@tug.dk`) provided the text for the danish option, Davide Giovanni Maria Salvetti (`salve@debian.org`) and Riccardo Murri (`murri@phc.unipi.it`) both provided the text for the italian option, and Sveinung Heggen (`sveinung.heggen@orkla.no`) provided the text for the norsk option.

As usual Rebecca Stiels improved the quality of this documentation.

References

- [1] Mats Dahlgren. `vrslon` – a \LaTeX Macro for version Numbering of Files.
CTAN:`tex-archive/macros/latex/contrib/supported/vrslon/vrslon.dtx`. \LaTeX 2 ϵ package.
- [2] Markus Kohm. The KOMA-timedate-bundle.
CTAN:`tex-archive/macros/latex/contrib/supported/koma-script/scrtime.dtx`.
 \LaTeX 2 ϵ package.
- [3] Robert Tolksdorf. Kennzeichnung von Vorversionen eines Dokuments.
CTAN:`tex-archive/macros/latex209/contrib/prelim/`. \LaTeX 2.09 package.

Change History

| v1.00 | | v1.10 |
|---|---------|--|
| General: New | 1 | General: <code>scrtime</code> instead of <code>printtim</code> 3 |
| v1.01 | | |
| General: Date added to <code>\NeedsTeXFormat</code> | . 1 | time option added 2 |

| | | | |
|---|---|--|---|
| v1.20 | | italian option added | 2 |
| General: french option added | 2 | | |
| scrttime option added | 2 | | |
| v1.21 | | General: norsk option added | 2 |
| General: Documentation improved | 1 | LPPL 1.3 | 1 |
| v1.22 | | | |
| General: Moved to LPPL | 1 | v2.00 | |
| v1.23 | | General: Complete rework to use the | |
| General: danish option added | 2 | kernel methods instead of everyshi . . . | 1 |